

Technical Specification

Product Code: CL012

Description: 10AX 2 Gang 2 Way Plate Switch



General Information

Dimensions (mm)	80 (W) x 80 (H) x 42 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
MiniGrid Plate (Gang)	1	
MiniGrid Single Width Module Quantity	2	
MiniGrid Double Width Module Quantity	1	
Style	Metal Clad	
Finish	Metal Clad Grey	
Insert Colour	White (WH)	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert & Rocker Switch: Urea
	Rear Housing: Nylon	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3.5	Terminal Torque Value (Nm) 0.5
Terminal Capacity - Solid (mm²)	4 x 1.5 or 2 x 2.5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	5 x Ø20	
Back Box Knockouts - Top (mm)	2 x Ø20	Back Box Knockouts - Sides (mm) 1 x Ø20
Back Box Knockouts - Bottom (mm)	1 x Ø20	Back Box Knockouts - Rear (mm) None
Back Box Earth Terminal Supplied	Yes	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Interchangeable with modules in the MiniGrid Range. Module colour to match is Click White (WH)

