

## iSpot Frameless CCT



### Description

Ideal for residential applications such as houses, drives and patios. Supplied with a remote control for switching on and off, dimming and changing the colour temperature.

Designed with an aesthetically appealing super slim body.

### Features

- Dimmable by remote control
- Remote control can cover up to 10 metre range and can control multiple fittings
- Air release valve to prevent condensation building up within fitting
- Frameless design improves IP rating
- Made from aluminium and tempered glass
- Driverless technology
- Angled bracket for easy installation
- Available in black
- Available with PIR option
- 3-year Guarantee

### Technical Specification

|                    |  |        |
|--------------------|--|--------|
| Voltage            | 220V-240V  |        |
| Frequency          | 50-60Hz  |        |
| Power Factor       | ≤0.9   |        |
| Colour Temperature | 3000K Warm White<br>4000K Cool White<br>5000K Daylight White |        |
| Beam Angle         | 110°   |        |
| Construction       | Aluminium Body & Tempered Glass                              |        |
| IP Rating          | IP65   |        |
| IK Rating          | IK07   |        |
| Cable length       | 50cm   |        |
| Dimmable           | Yes  |        |
| Light Source       | Non-replaceable LED  |        |
| Lifespan           | 30,000hrs  |        |
| Luminous Flux      | 10W  | 900lm  |
|                    | 20W  | 180lm  |
|                    | 30W  | 2700lm |
|                    | 50W  | 4500lm |
| Luminous Efficacy  | 90 lm/W  |        |
| Standards          | BS EN 60598-1  |        |

No user serviceable parts

### Range

|        |                                   |
|--------|-----------------------------------|
| I2014B | 10W iSpot CCT Floodlight          |
| I2015B | 10W iSpot CCT Floodlight with PIR |
| I2024B | 20W iSpot CCT Floodlight          |
| I2025B | 20W iSpot CCT Floodlight with PIR |
| I2034B | 30W iSpot CCT Floodlight          |
| I2035B | 30W iSpot CCT Floodlight with PIR |
| I2044B | 50W iSpot CCT Floodlight          |
| I2045B | 50W iSpot CCT Floodlight with PIR |

### PIR Specification

|                     |                             |
|---------------------|-----------------------------|
| Detection Range     | 8m±2m                       |
| Detection Angle     | 120°                        |
| Time Delay          | 10sec ±5sec – 8min<br>±2min |
| Ambient Light       | 5-2000 lux                  |
| Installation Height | 1.8m – 2.5m                 |

### Dimensions

|       | Length | Width | Height |
|-------|--------|-------|--------|
| I2012 | 120mm  | 20mm  | 104mm  |
| I2022 | 120mm  | 20mm  | 163mm  |
| I2032 | 163mm  | 20mm  | 135mm  |
| I2042 | 163mm  | 20mm  | 191mm  |
| I2013 | 195mm  | 20mm  | 159mm  |
| I2023 | 195mm  | 20mm  | 215mm  |
| I2033 | 223mm  | 20mm  | 184mm  |
| I2043 | 235mm  | 20mm  | 239mm  |

All dimensions are body and do not include the bracket

Contact your local authority for information concerning the correct disposal of your product.