

Upgrade
Apr. 2023

Della

(80W, 100W, 150W, 200W, 300W)

High power LED flood light

Built-in motion sensor 


Wildlife friendly* 

*CCT of 4000K or lower


- Models available with asymmetric optic lens
 - Diecast aluminium body
 - Long life of 40,000hrs
 - Surge protection
 - Adjustable PIR sensor
- 1m of H05RN-F 3 x 1.0mm² cable



DEL300



110°x110°



Asymmetric 50°

Order Code	Power	Finish	Beam Angle	CCT	Lumen	Trade Price
DEL80	80W	Black	110°	6500K	8000lm	£136.22
			Asymmetric 50°	4000K	8800lm	£146.32
DEL100	100W	Black	110°	6500K	9000lm	£141.89
			Asymmetric 50°	4000K	11000lm	£151.67
DEL150	150W	Black	110°	6500K	15500lm	£278.11
			Asymmetric 50°	4000K	16500lm	£292.74
DEL200	200W	Black	110°	6500K	20000lm	£334.86
			Asymmetric 50°	4000K	22000lm	£360.05
DEL300	300W	Black	Asymmetric 50°	4000K	33000lm	£614.25

Sensor Options

Order Code	Power	Beam Angle	CCT	Lumen	Trade Price
DEL80-W65/S	80W	110°	6500K	8000lm	£187.69
DEL100-W65/S	100W	110°	6500K	9000lm	£209.42

Accessory

Type	Order Code	Description	Trade Price
Connector	KCWP3IN	IP67 In-line Connector	£11.05

5 5 Years Product Warranty

2 2 Years On-Site Warranty

2000V Surge Protection (L to GND)



Ceiling mount bracket
↳ P215



Optional Connector
KCWP3IN

General Specification


Voltage	220-240Vac 50/60Hz
CRI	>80
Life Time	40,000h
Power Factor	>0.96
Ambient Temp	-20°C to 40°C
Housing	Diecast aluminum




Order Code

DEL80-W65
DEL80-A40
DEL100-W65
DEL100-A40
DEL150-W65
DEL150-A40
DEL200-W65
DEL200-A40
DEL300-A40
DEL80-W65/S
DEL100-W65/S


Dimensions




282mm
DEL80
DEL100



332mm
DEL150



382mm
DEL200



444mm
DEL300